

# SOP Range Buckets

Light material high dump buckets SOP range are for the wheel loaders from operating weight 18 t (39 lb) up to 64 t (140 lb). Buckets dumping cylinders are located on the sidewalls which gives a full empty space inside the bucket without any beams or other parts.

This style of construction will avoid material freezing inside at wintertime and material will move easily in and out of the bucket.

Buckets cylinders have inside oil suspension for both ends.

Buckets unloading heights are increased about 1500 mm (59 in).

Buckets dimensions are shown with bolt-on edges as standard.



## Technical specification

Product Code	Volume		Width		Depth		Height		Weight		Maximum material density	
	m <sup>3</sup>	yd <sup>3</sup>	mm	in	mm	ft in	mm	ft in	kg	lb	kg/m <sup>3</sup>	lb/yd <sup>3</sup>
<b>210080SOP</b>	8,0	10,4	3200	125"	1790	5'10"	2020	6'7"	3300	7,270	1000	1,680
<b>210100SOP</b>	10,0	11,3	3700	146"	1900	6'3"	2050	6'9"	3600	7,940	1000	1,680
<b>210110SOP</b>	11,0	14,3	3700	146"	1900	6'3"	2150	7'0"	3900	8,600	1000	1,680
<b>210120SOP</b>	12,0	15,6	3700	146"	2000	6'6"	2280	7'6"	4400	9,700	1000	1,680
<b>210130SOP</b>	13,0	16,9	3700	146"	2030	6'8"	2350	7'8"	4700	10,360	900	1,510
<b>210140SOP</b>	14,0	18,2	3700	146"	2230	7'4"	2520	8'3"	5600	12,330	900	1,510
<b>210150SOP</b>	15,0	19,5	4000	157"	2230	7'4"	2520	8'3"	5900	13,010	900	1,510
<b>210170SOP</b>	17,0	22,1	4000	157"	2320	7'7"	2630	8'7"	6500	14,310	900	1,510
<b>210200SOP</b>	20,0	26	4000	157"	2500	8'2"	2690	8'10"	6800	14,970	900	1,510