

Standard Buckets

Standard light material high dump buckets are for all the wheel loaders with operating weight up to 64 t (140 lb). Buckets dumping cylinders are located in the middle which gives to bucket lighter weight because of smaller and lighter frame.

Cylinders are in vertical position and they have inside oil suspension for both ends. Buckets unloading heights are increased about 1500 mm (59 in).

Buckets are with straight welded cutting edge and bolt-on edges are an option.



Technical specification

Product Code	Volume		Width		Depth		Height		Weight		Maximum material density	
	m ³	yd ³	mm	in	mm	ft in	mm	ft in	kg	lb	kg/m ³	lb/yd ³
20030	3,0	3,9	2550	100"	1500	4'11"	1400	4'7"	1550	3,410	1000	1,680
20040	4,0	5,2	2550	100"	1670	5'6"	1670	5'6"	1700	3,740	1000	1,680
20050	5,0	6,5	2750	108"	1730	5'7"	1730	5'7"	1900	4,180	1000	1,680
20055	5,5	7,2	3000	118"	1730	5'7"	1730	5'7"	2000	4,410	1000	1,680
20060	6,0	7,9	3000	118"	1770	5'4"	1770	5'4"	2100	4,630	1000	1,680
20070	7,0	9,2	3000	118"	1900	6'3"	1900	6'3"	2300	5,060	1000	1,680
20080	8,0	10,5	3200	125"	2000	6'6"	2000	6'6"	2450	5,390	1000	1,680
20090	9,0	11,8	3500	136"	2000	6'6"	2000	6'6"	2550	5,620	1000	1,680
20100	10,0	13,1	3500	136"	2100	6'9"	2100	6'9"	2750	6,050	1000	1,680
20110	11,0	14,3	3700	146"	2150	7'0"	2150	7'0"	3000	6,610	900	1,510
20120	12,0	15,6	4000	156"	2150	7'0"	2150	7'0"	3550	7,810	900	1,510
20130	13,0	16,9	4000	156"	2300	7'6"	2300	7'6"	3750	8,260	900	1,510
20150	15,0	19,5	4000	156"	2400	7'9"	2450	8'0"	4500	9,910	900	1,510
20170	17,0	22,1	4000	156"	2520	8'3"	2520	8'3"	5200	11,450	900	1,510
20200	20,0	26,0	4500	176"	2520	8'3"	2520	8'3"	6300	13,870	900	1,510